



Foundations for a new school, Takanini, Auckland, NZ

Both TTT Deep Pile Foundations and TTT Raft Foundations were used to provide foundation solutions for several timber-floored buildings for a new school.



Deep Pile Foundations & Raft Foundations

Project background: Foundations for a new school, Takanini, Auckland, NZ

- Foundations were required for new school buildings (blocks).
- TTT offered two solutions – Deep Pile Foundations and Raft Foundations – using TTT MultiPoles.
- The site was located in an ancient Kauri swamp with 50m of peat underfoot.
- The project commenced in 2016.

Project challenge:

- The foundations for all blocks needed to be able to handle both tension and compression earthquake loads concentrated in several points due to the use of portal frames in the superstructure above.
- The ground consisted of 50m of soft, compressible peat with intermediate lenses (thin layers) of dense sand which meant a very weak soil structure with negligible support.
- The ground water table was 300mm below ground level.
- The client had requirements over and above the building regulations that had to be met in terms of future expected settlements and the surrounding ground considerations.
- Shallow foundations suitable for 60kPa Geotechnical Ultimate Bearing Capacity were required.
- The first stage of the school needed to be opened as soon as possible which meant that several blocks were being installed at the same time – the site was busy and tight for space.
- Installation needed to be rapid.

The TTT MultiPole solution:

- TTT Uglie MultiPoles, 250–350mm SED, were used as friction piles providing a Deep Pile Foundation, and installed down to depths of up to 30m using sections from 4.8m to 12.0m joined with proprietary MultiPole Connectors.
- The Deep Pile Foundations relied on a combination of skin friction and end bearing to provide resistance to tension and compression earthquake loads.
- The unique hollow core of the TTT MultiPoles allowed for fast installation via vibration and pile driving.

- TTT Raft Foundations were considered light enough for the low bearing capacity of the ground.
- The Raft Foundations had concrete-topped sections which provided resistance to tension earthquake loads.
- All foundation solutions were engineered, designed, and peer-reviewed.
- Future housing and infrastructure development in the area was taken into account during design to allow for future predicted ground settlement.
- Static load testing was carried out on several occasions to verify the performance of the foundations to twice the Ultimate Limit State (ULS) loads.
- Several blocks, completed and in use, had their floor levels monitored for the first 6 months to verify that the foundation settlements were within the required parameters.



Case Study CRF02:Nov17 | ©TTT Products Christchurch Ltd. | Page 2 of 2

Postal address

TTT Products Christchurch Ltd
PO Box 99
Tuakau 2342
New Zealand

Details

Freephone: 0800 864 564
Phone: +(64) 9 236 8880
Fax: +(64) 9 236 8663

Talk to us
0800 864 564

Cliff Monk

Mobile: +(64) 27 514 4427
cliff.monk@unilog.co.nz

Marshall Bryce

Mobile: +(64) 27 587 5621
marshall.bryce@unilog.co.nz

TTT, MultiPole, Uglies, and UniLog are trademarks of Fellrock Developments Limited.

TTT MultiPole